


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : A01K 1/12, 1/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/41977</p> <p>(43) International Publication Date: 26 August 1999 (26.08.99)</p>
<p>(21) International Application Number: PCT/NL99/00081</p> <p>(22) International Filing Date: 16 February 1999 (16.02.99)</p> <p>(30) Priority Data: 1008334 18 February 1998 (18.02.98) NL</p> <p>(71) Applicant (for all designated States except US): PROLION B.V. [NL/NL]; Kromme Spieringweg 289 b, P.O Box 34, NL-2140 AA Vijfhuizen (NL).</p> <p>(72) Inventor; and</p> <p>(75) Inventor/Applicant (for US only): DESSING, Jacobus, Petrus, Maria [NL/NL]; Kruisweg 1483, NL-2142 La Cruquius (NL).</p> <p>(74) Agent: UITTENBOGAART, Gustaaf, Adolf; Indeig B.V., P.O. Box 3, NL-2050 AA Overveen (NL).</p>		<p>(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. In English translation (filed in Dutch).</i></p>

(54) Title: DEVICE AND METHOD FOR THE AUTOMATIC MILKING OF ANIMALS



(57) Abstract

The invention relates to a milking device and method for the automatic milking of animals in a milking parlour. The animals are housed in a dwelling area with dwelling stalls (11) which are suitable for permanent housing and are provided with boundary means, operated by control systems, for confining an animal. In order to prevent soiling of the aisles in the dwelling area, the milking device may comprise means for shortening the time that animals to be milked are present in the aisle.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Device and method for the automatic milking of animals

The invention relates to a milking device for the automatic milking of animals according to the preamble
5 of Claim 1.

Such a device is known from EP 0270165, which describes a milking device for cows which is constructed on a free stall housing. In such a free stall housing, free stalls, where the animals can rest,
10 are provided, and there is a walking area in which the animals move around when they are not in the free stall housing. The walking area is designed in such a way that droppings deposited there by the animals can be removed in a simple manner, for example by having
15 manure pits provided at various points in the floor. The floor is also constructed in a special way. In the case of many existing milking parlours, which are tie-up cowsheds, this construction is not present. In the case of these tie-up cowsheds the floor is of a totally
20 different design and is not suitable for allowing the animals to move around freely on the aisles. The object of the invention is to make the tie-up cowsheds suitable for use with a milking parlour in which the milking is automatic.

25 For this purpose, according to the invention the milking device is designed according to the characterizing part of Claim 1. By using dwelling stalls, in which the animals to be milked can stay more or less permanently and can be confined by the control
30 system, it is possible to make the animals go to the milking parlour at certain times which are determined by the control system. This means that they are in the aisle for only a short time, so that the aisle is hardly soiled at all with manure and the like.

35 According to a further improvement, the device is designed according to Claim 2. By this measure, it is

possible in a simple manner to confine an animal in the dwelling stall.

According to another embodiment, the device is designed according to Claim 3. By this measure, a
5 saving can be made on the costs of the boundary means.

According to one embodiment, the milking device is designed according to Claim 4. By this measure, the control on the behaviour of the animals is improved, so that, for example, it can be better recorded which
10 animals have gone to or are near the milking parlour and, if problems are found, for example during the milking, it is also known in which parlour the animal concerned is confined.

According to one embodiment, the milking device is
15 designed according to Claim 5. By this measure, after the dwelling stalls have been opened for a group of animals, the animals are guided to the entrance of the milking parlour, where they are milked and, after they have left the milking parlour, are guided to an empty
20 dwelling stall. In this case as many animals as are released in one go from the dwelling stalls will generally be able to stay in the area between the entrance means and the milking parlour.

According to a further improvement, the milking
25 device is designed according to Claim 6. By this measure, the number of animals that is released in one go from a dwelling stall can be greater than the number of animals that can go into the milking parlour in one go.

30 According to a further improvement, the milking device is designed according to Claim 7. By this measure, the entrance or the exit is cleared in a simple manner.

According to one embodiment, the device is
35 designed according to Claim 8. By this measure, the

- 3 -

length of the aisle can be shortened, so that the animals are guided better to the dwelling stall or to the milking parlour.

According to one embodiment, the milking device is
5 designed according to Claim 9. By this measure, it is ensured that the animals do not stand unnecessarily in the aisle, so that the capacity of the device is not thereby restricted.

The invention also comprises a method according to
10 the preamble of Claim 10. Such a method is known from US 4010714. This document shows a device in which the animals to be milked stand in a parlour and an automatic milking device is placed under each animal to be milked. Special and expensive structural facilities
15 are necessary for this, which is a disadvantage.

In order to avoid this disadvantage, the method is carried out according to the characterizing part of Claim 10. In this case the dwelling stalls of a number of animals to be milked are opened periodically, and
20 the animals are confined again after milking. In this way, the advantages of milking in a milking parlour are combined with the structural facilities of existing tie-up cowsheds.

According to an improvement, the method is carried
25 out according to Claim 11 or 12. By this measure, the milking can be carried out without supervision.

According to a further improvement, the method is carried out according to Claim 13. By this measure, the equipment present in the milking parlour is used as
30 efficiently as possible.

According to one embodiment of the method, the method is carried out according to Claim 14. By this measure, the capacity of the device is increased and soiling of the aisles is avoided as far as possible.

The invention will be explained below with reference to a drawing, in which:

Figure 1 shows a diagrammatic top view of a first embodiment of a tie-up cowshed with an automatic milking device;

Figure 2 shows a diagrammatic top view of a second embodiment of a tie-up cowshed with an automatic milking device;

Figure 3 shows detail III from Figures 1 and 2; and

Figure 4 shows view IV-IV from Figure 3.

In the various figures, corresponding components are indicated as far as possible by the same reference numerals.

Figure 1 shows a shed 1, which serves as a dwelling area for cows to be milked, and which has therein two rows of dwelling stalls 11, in which the cows stand with their tails facing each other. A feed passage 17 is provided between the long wall of the shed 1 and a row of dwelling stalls 11. An aisle 9 runs between the two rows of dwelling stalls 11. The dwelling stalls 11 are designed in such a way that a cow can enter or leave the dwelling stall 11 by way of the aisle 9. While it is in the dwelling stall 11, the cow can take feed from the feed passage 17. The feed passage 17 is bounded by a barrier 10. The shed is provided with doors 18.

A manure channel 12 is provided along the rear side of the dwelling stalls 11, in the longitudinal direction of the aisle 9. While it is in the dwelling stall 11, the cow will produce droppings, which fall into this manure channel 12. In order to be able to remove these droppings from the manure channel 12, a manure slide 13 is provided in a known manner, by means of which manure slide the droppings are conveyed through an opening in the wall of the shed 1 and

deposited in a known manner on one of the manure heaps 19, which are situated behind the shed.

On the other short side of the barn 1, facilities are provided for milking the animals present in the barn. These facilities consist of a milking parlour 2 with an entrance barrier 4 and an exit barrier 5. Milking equipment 3 for milking the cows is placed in the milking parlour 2. The milking equipment 3 may comprise means for the automatic fitting of teat cups around the teats of a cow present in the milking parlour 2. The milking equipment 3 can, if desired, function without supervision, by means of a control system. For this purpose, the device is designed in such a way that the cows to be milked can go into the milking parlour 2 and be milked there without human intervention.

At the entrance barrier 4 there is a waiting area for cows to be milked 6, and at the exit barrier 5 there is a waiting area for milked cows 7. The waiting areas 6 and 7 are dimensioned in such a way that a small number of cows can always be released simultaneously from the dwelling stalls 11, for example 4 or 6 cows, which then await their turn in the waiting area for cows to be milked 6. After milking, the cows can wait a moment in the waiting area for milked cows 7, or can return immediately to their dwelling stalls 11. After the last cow has returned to its dwelling stall 11, they are confined again in the manner discussed below, and the following group of cows is released from the dwelling stalls.

In order to ensure that the cows can find their way quickly along aisle 9 to their dwelling stalls, the length of the aisle 9 can be adapted by means of a barrier 16 which is movable in the longitudinal direction of the aisle 9. In order to ensure that the

- 6 -

animals do not remain standing for a long time in the aisle 9, a herding bar 14 is movable in the longitudinal direction of the aisle 9. Chains 15 hang from the herding bar 14, which chains can touch the cows in the aisle 9 and possibly in the dwelling stall 11, causing them to move in the direction of movement of the herding bar 14. By means of the herding bar 14, the animals can be driven from the dwelling stalls to the waiting area for animals to be milked 6, or from the waiting area for milked animals 7 to the dwelling stalls 11.

In an alternative embodiment, instead of the single milking parlour 2 with one or two waiting areas 6 and 7, a number of milking parlours can be used, as many as there are animals released simultaneously. The milking parlours can be grouped in many known ways, for example in a row, herringbone, in tandem, and also as a carrousel, the choice depending primarily on the desired capacity. It is also possible not to have both waiting areas 6 and 7, but for only one waiting area to be present. In that case the animals can go, for example, directly from the dwelling stall 11 to the milking parlour 2 and return as a group, or if they are driven in a group to the waiting area 6, they can return directly from the milking parlour 2 to the dwelling stall 11.

It is assumed above that a milked animal returns to the dwelling stall 11 from which it has come, but this is not necessary. It is possible to shorten waiting times by using a number of empty dwelling stalls 11 as a new dwelling area for milked animals.

Figure 2 shows a milking device which is comparable to that of Figure 1, in which milking device the feed passage 17 has been placed between the two rows of dwelling stalls 11, so that there are now two

- 7 -

aisles 9, each provided with a movable barrier 16 and a herding bar 14. The cows stand with their heads facing each other. In this embodiment the swing barrier 8 is a double barrier, so that both the waiting area for cows to be milked 6 and the waiting area for milked cows 7 can be shut off at the same time. This means that the freedom of movement of the cows on the aisle 9 is restricted, with the result that the soiling there is reduced.

10 The dwelling stalls 11 are shown in greater detail in Figures 3 and 4. The dwelling stalls 11 are bounded on the long side by a partition barrier 20 and at the side facing the feed passage 17 by an end barrier 21. Said end barrier 21 permits eating from the feed
15 passage 17, but impedes the passage of an animal in the dwelling stall 11. The animals are confined in the dwelling stall 11 by means of a confining barrier 22, which is operated by an air cylinder 23. In the embodiment shown, four dwelling stalls 11 are shut off
20 simultaneously by the confining barrier 22. However, it is also possible for the confining barrier 22 to be designed in such a way that other numbers of dwelling stalls 11 are shut off simultaneously, or that each dwelling stall 11 can be shut off separately. In the
25 embodiment shown, the confining barrier 22 is in the form of a U-shaped frame. Examples of other embodiments are swing barriers or a chain which is tensioned. Apart from the confining barrier 22 shown here, other means are also possible for confining an animal in the
30 dwelling stall 11.

 A presence sensor (not shown) can be accommodated in the dwelling stall 11, by means of which presence sensor it can be established whether a cow to be milked or a milked cow has left the dwelling stall 11 and
35 returned again. If desired, the cow could be provided

with electronic identification means, in order to establish its identity in the milking parlour 2. These electronic identification means can also be used to establish whether the animal is back in the dwelling stall 11, and to establish which animal is in a particular dwelling stall 11. It can then also be known in the control system where a particular animal is, so that it can be found easily, for example in cases of sickness or the like.

10 The device is controlled by a control system which is combined, for example, with the control system of the milking equipment 3. In the control system the movements of the cows in the aisles 9 are followed, and procedures can be incorporated for controlling the
15 herding bar 14, the swing barrier 8 and a movable barrier 16, depending on the movements of the animals. The cows to be milked are influenced in such a way by this that their duration of stay in the aisles 9 is as short as possible, with the result that the latter are
20 soiled as little as possible. By periodically opening the dwelling stalls 11 of a limited number of animals and making these animals move to the milking parlour 2, it is ensured that they can be milked there by the automatic milking equipment 3 without supervision.

Claims

1. Milking device for the automatic milking of animals, comprising a milking parlour (2) provided with milking equipment (3), a dwelling area (1) provided with dwelling stalls (11) for housing animals to be milked, an aisle (9) between the dwelling stalls and the milking parlour, and barriers for guiding animals to be milked from the dwelling area to and from the milking parlour, characterized in that the dwelling stalls (11) are suitable for permanent residence of the animals to be milked and are provided with boundary means (22) operated by a control system, for confining an animal.
2. Milking device according to Claim 1, characterized in that the boundary means comprise a movable barrier (22).
3. Milking device according to Claim 1 or 2, characterized in that the boundary means can confine animals in several dwelling stalls simultaneously.
4. Milking device according to Claim 1, 2 or 3, characterized in that the dwelling stalls are provided with means for establishing the presence of an animal and possibly the identity of the animal present.
5. Milking device according to one of the preceding claims, in which the milking parlour (2) is provided with an entrance (4) and an exit (5), characterized in that the barriers comprise entrance means (8) operated by the control system, for alternately placing the aisle (9) in communication with the entrance (4) or the exit (5) of the milking parlour (2).
6. Milking device according to Claim 5, characterized in that a waiting area (6, 7) is provided at least at the entrance (4) or the exit (5) of the milking parlour (2).

- 10 -

7. Milking device according to Claim 5 or 6, characterized in that the entrance means comprise a swing barrier (8).
8. Milking device according to one of the preceding
5 claims, characterized in that on the side facing away from the milking parlour (2) the aisle (9) is bounded by a barrier (16) which is movable by the control system.
9. Milking device according to one of the preceding
10 claims, characterized in that the aisle (9) is provided with herding means (14, 15) which are operated by the control system.
10. Method for the automatic milking of animals in a milking parlour (2), in which the animals are confined
15 more or less permanently in dwelling stalls (11), characterized in that the confinement of a number of animals to be milked is periodically interrupted, after which these animals can leave the dwelling stall (11) and are guided to the milking parlour (2), and are
20 confined again in a dwelling stall (11) after milking.
11. Method according to Claim 10, characterized in that the animals to be milked are guided to the milking parlour (2) by the automatic movement of barriers (4, 8, 16, 22).
- 25 12. Method according to Claim 10 or 11, characterized in that the milked animals are guided from the milking parlour (2) to a dwelling stall (11) by the automatic movement of barriers (5, 8, 16, 22).
13. Method according to Claim 10, 11 or 12,
30 characterized in that, before and/or after milking, the animals are guided into a waiting area (6, 7), in order to make an aisle (9) between the milking parlour (2) and the dwelling stalls (11) available for other animals.

14. Method according to one of Claims 10-13,
characterized in that the animals are stimulated to
move after the interruption of the confinement in the
dwelling stall (11), after leaving the milking parlour
5 (2) and/or after leaving the waiting area (7).




Fig. 1






Fig. 2

*Fig. 3**Fig. 4*

INTERNATIONAL SEARCH REPORT

Inter national Application No

PCT/NL 99/00081

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A01K1/12 A01K1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A01K A01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 636 313 A (MAASLAND NV) 1 February 1995 see column 3, line 45 - column 6, line 38 see claims; figures ---	1,4,5,7, 10,14
A	EP 0 753 249 A (MAASLAND NV) 15 January 1997 see column 2, line 26 - column 3, line 41 see claims; figures --- -/--	1,5, 7-10,14



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

21 May 1999

Date of mailing of the international search report

01/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pirou, J-C

INTERNATIONAL SEARCH REPORT

Inter. Appl. Application No

PCT/NL 99/00081

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	NL 8 104 807 A (WOPEREIS AGRARISCHE SYSTEMEN B) 4 January 1982 see claims; figures & DATABASE WPI Week 8205 Derwent Publications Ltd., London, GB; AN 82-b1155e & NL 8 104 807 A (WOPEREIS) see abstract ----	1,10,14
A	US 4 445 460 A (STENCIL GERALD R) 1 May 1984 see claims; figures ----	1,10,14
A	US 4 977 856 A (NORWOOD EUGENE E) 18 December 1990 see claims; figures ----	1,3,10
A	EP 0 635 206 A (TEXAS INDUSTRIES INC) 25 January 1995 see claims; figures ----	1,10
A	EP 0 270 165 A (MULTINORM BV) 8 June 1988 cited in the application see claims; figures ----	1,10
A	US 4 010 714 A (NOTSUKI IWA O ET AL) 8 March 1977 cited in the application see claims; figures ----	1,10
A	WO 96 03031 A (PROLION BV ;OOSTERLING PIETER ADRIAAN (NL)) 8 February 1996 see claims; figures -----	1,10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/NL 99/00081

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0636313 A	01-02-1995	NL 9301317 A DE 69417313 D	16-02-1995 29-04-1999
EP 0753249 A	15-01-1997	NL 1000782 C DE 69601199 D	14-01-1997 04-02-1999
NL 8104807 A	04-01-1982	NONE	
US 4445460 A	01-05-1984	NONE	
US 4977856 A	18-12-1990	NONE	
EP 0635206 A	25-01-1995	NL 9301261 A	16-02-1995
EP 0270165 A	08-06-1988	NL 8602942 A AT 156969 T AU 596466 B AU 8135287 A DE 3752107 D DE 3752107 T DK 606487 A EP 0432148 A US 4889074 A	16-06-1988 15-09-1997 03-05-1990 26-05-1988 25-09-1997 18-12-1997 20-05-1988 12-06-1991 26-12-1989
US 4010714 A	08-03-1977	JP 881497 C JP 50121080 A JP 52012108 B JP 984730 C JP 50121078 A JP 54013394 B	13-09-1977 22-09-1975 05-04-1977 29-01-1980 22-09-1975 30-05-1979
WO 9603031 A	08-02-1996	NL 9401238 A CA 2196089 A DE 69505133 D DE 69505133 T EP 0772389 A EP 0853875 A JP 10503088 T US 5782199 A	01-03-1996 08-02-1996 05-11-1998 18-02-1999 14-05-1997 22-07-1998 24-03-1998 21-07-1998